



Type K/J

These well-made units have exceptional accuracy for thermocouple thermometers, fast response times, high 0.1°F/C resolution (-200 to 800°C), and wide measurement ranges. Features include min/max, relative temperature, auto power off, and hold functions. Meters have large, easy-to-read 3½" LCD, and accept standard thermocouple probes. Comes ready to use with carrying cases, beaded wire probes, and batteries. Can also be used with optional AC Adapter 800003. N.I.S.T. Traceable Certificate of Compliance available.

DIM: 7¼" × 2½" × 1¼" (184 × 64 × 32 mm). WEIGHT: 7.4 oz (210 g).

No.	Description
800005	Thermometer Advanced
800005C	Thermometer Advanced. Certified
800060-97	Type K & J Thermocouple Probes
800005S	Thermolink Software
800001USB	USB Cable
800001	RS232 71" Cable
840094	RS232 to USB Adaptor Cable
800003	AC Adapter
840089	Rubber Holster
840094	Field Tripod

	Range	Resolution	Accuracy
Type K	-200 to 1370°C	-200 to 800°C = 0.1°C 800 to 1370°C = 1°C	±(0.1% reading + 0.7°C)
	-328 to 2498°F	-328 to 1000°F = 0.1°F 1000 to 2498°F = 1°F	±(0.1% reading + 1.4°F)
Type J	-200 to 760°C	-200 to 600°C = 0.1°C 600 to 760°C = 1°C	±(0.1% reading + 0.7°C)
	-328 to 1400°F	-328 to 1000°F = 0.1°F 1000 to 2498°F = 1°F	±(0.1% reading + 1.4°F)

