



**Rugged, reliable, accurate**

- Shockproof
- IP67 Waterproof
- Floats
- Also accepts standard BNC probes
- Rechargeable Lithium-Ion battery
- Protective soft-grip outer layer

AquaShock® meters have been designed and tested to ensure accurate, reliable water quality measurement under any conditions. Results are easy to read, in any light, on the large LED backlit display. Powered by a long-lasting, environmentally friendly, rechargeable Lithium-Ion battery. AquaShock® meters are very intuitive and include all the functions you will likely ever need, including: review of 99 memories (min/max/ave) directly on the meter's display, internal clock and calendar, temperature in °C or °F, auto-ranging, automatic and manual temperature compensation, and hold.

AquaShock® is virtually unbreakable, eliminating the inconvenience of frequent instrument repair or replacement for at least 5 years of uninterrupted, accurate, reliable use.



**pH Kit**

- Measures pH, mV and temperature
- 5 calibration points
- Automatic buffer recognition
- Recalls electrode offset, slope and last calibration

Includes AquaShock® pH Meter 850057; AC adaptor; manual; warranty card; probe input covers; ATC pH probe; pH buffers 4, 7, 10 & deionized water; protective, foam-lined, hard-shell carrying case.

METER DIM: 7¾" x 3¾" x 2¾" (197 x 95 x 70 mm).

METER WEIGHT: 1 lb (454 g).

KIT DIM: 13½" x 11¼" x 3" (343 x 286 x 76 mm).

Mode	pH	Temperature	mV
Range	0 to 14 pH	32 to 140°F (0 to 60°C)	-1999 to 1999 mV
Resolution	0.01 pH	0.1°F/C	0.1 mV
Accuracy	±0.01 pH	0.9°F (±0.5°C)	±0.3 mV

**pH/ORP Kit**

- Measures pH, mV & ORP (Oxygen Reduction Potential) and temperature
- 5 calibration points
- Automatic buffer recognition
- Recalls electrode offset, slope and last calibration

Includes AquaShock® pH/ORP Meter 850064; ATC pH probe; AC adaptor; manual; warranty card; probe input covers; pH buffers 4, 7, 10 & deionized water; protective, foam-lined, hard-shell carrying case.

METER DIM: 7¾" x 3¾" x 2¾" (197 x 95 x 70 mm).

METER WEIGHT: 1 lb (454 g).

KIT DIM: 13½" x 11¼" x 3" (343 x 286 x 76 mm).

Mode	pH	Temperature	mV
Range	0 to 14 pH	32 to 140°F (0 to 60°C)	-1999 to 1999 mV
Resolution	0.01 pH	0.1°F/C	0.1 mV
Accuracy	±0.01 pH	0.9°F (±0.5°C)	±0.3 mV

**No. Description**

<b>850057K</b>	<b>AquaShock® pH Kit</b>
850057P	AquaShock® ATC pH Replacement Probe
<b>850064K</b>	<b>AquaShock® pH/ORP Kit</b>
850064P	AquaShock® ORP Probe
860008	pH 4, 3 bottles, 40 ml Each
860009	pH 7, 3 bottles, 40 ml Each
860010	pH 10, 3 bottles, 40 ml Each
860011	Deionized Water, 3 bottles, 40 ml
860012	pH Buffer Set, pH 4, pH 7, pH 10, 40ml Each
840093	Field Tripod



U.S. PATENT 8,480,428